

22786

IN THE U.S. PATENT AND TRADEMARK OFFICE

Inventor Martin KRISTEN  
Patent App. 10/848,832  
Filed 18 May 2004  
For CHAIR WITH SWING-OUT FOOTREST

Art Unit 3636  
Hon. Commissioner of Patents  
Box 1450  
Alexandria, VA 22313-1450

Certificate of Express or First-Class Mailing  
I hereby certify that I have deposited this correspondence with the US Postal Service as first-class or, if a mailing-label number is given below, as express mail addressed to Comm. of Patents, Box 1450, Alexandria, VA 22313-1450 on

AUG 23 2005

EV701300388

Conf. No. 4791

Examiner Nelson jr., M


Allowed: 13 April 2005

RESPONSE TO NOTICE OF DRAWING INCONSISTENCY WITH SPECIFICATION

In the above-identified matter the originally filed Specification described the view of FIG. 7 on page 5 (copy attached) and then on page 7 (copy also attached) discussed this figure in detail. Thus there is no drawing inconsistency.

If there are any further questions in this regard, the Office is invited to telephone the undersigned to discuss the matter.

Respectfully submitted,  
The Firm of Karl F. Ross P.C.

  
by: Andrew Wilford, 26,597  
Attorney for Applicant

22 August 2005  
5676 Riverdale Avenue Box 900  
Bronx, NY 10471-0900  
Cust. No.: 535  
Tel: (718) 884-6600  
Fax: (718) 601-1099  
Enclosure:

Pages 5 & 7 of original Specification

## BRIEF DESCRIPTION OF THE DRAWING

The above and other objects, features, and advantages will become more readily apparent from the following description, reference being made to the accompanying drawing in which:

5           FIGS. 1, 2, and 3 are side sectional views showing the mechanism of the chair according to the invention in retracted, partially extended, and fully extended positions, the upholstered parts of the chair being omitted for clarity of view;

10           FIG. 4 is a top view of the foot-rest mechanism in the fully-extended position;

          FIGS. 5 and 6 are side and top views of the mechanism shown in FIG. 4; and

          FIG. 7 is a view of a detail of the foot rest.

## SPECIFIC DESCRIPTION

15           As seen in FIGS. 1 to 5, a chair according to the invention has a stationary frame or base 1 generally symmetrical to a central vertical plane P and having a pair of side base plates 2 symmetrically flanking the plane P below a seat plate 3. A back 4 projects upward from a rear end of the seat plate 3.  
20           The seat plate 3 and back 4 can also move, but their movements are not relevant to the instant invention.

          A footrest 5 is carried on a mounting plate 18 at an outer end of a pair of arms 8 that symmetrically flank the plane

An actuator 13 that can be powered electrically, hydraulically, or pneumatically has an output element 16 pivoted to an inner end of a link 12 whose outer end is pivoted at an axis 29 to the link 7 at the bracket 17 between the axes 27 and 28. A crank arm 15 has an inner end pivoted at 14 on the base 1 and an outer end pivoted at 29 on the element 16 and link 12 to force this axis 29 to move along an arcuate path as the element 16 moves out (to the left in FIGS. 1 to 3) and in (to the right in FIGS. 1 to 3).

FIG. 7 shows how an upholstered footrest cushion 24 is provided with a pair of mounting rods 26 (only one shown) that fit in clips 25 carried on the footrest support 18. Thus if a user's leg gets caught between the footrest cushion 24 and the base 1 when the footrest 5 is being lowered, the cushion 24 will disconnect from the support 18 and not injure the user.